

# JIS G3459 一般配管用不銹鋼鋼管

單位：元/每米

( )%

吋吋稱呼 平均外徑	厚度	單價	SCH.#	吋吋稱呼 平均外徑	厚度	單價	SCH.#	吋吋稱呼 平均外徑	厚度	單價	SCH.#				
1/8" 10.5mm	1.2m/m	48	10S	2" 60.5mm	2.0m/m	353	10S	5" 139.8mm	2.5m/m	1,065					
	1.5m/m	60	20S		2.5m/m	429				3.0m/m	1,250				
1/4" 13.8mm	1.2m/m	59	5S		2.8m/m	501				3.4m/m	1,530	10S			
	1.5m/m	73			3.0m/m	501				3.5m/m	1,530				
3/8" 17.3mm	1.5m/m	93			3.5m/m	621			20S	4.0m/m	1,680				
	2.0m/m	110	20S		3.9m/m	679			40S	5.0m/m	2,265	20S			
20.4mm	2.0m/m	112			4.0m/m	679				6.0m/m	2,695				
	2.5m/m	133			2 1/2" 76.3mm	2.0m/m			447	10S	6" 165.2mm	6.6m/m	3,054	40S	
1/2" 21.7mm	2.0m/m	120				2.5m/m			545				3.0m/m	1,485	
	2.1m/m	126	10S			3.0m/m			638				3.5m/m	1,815	10S
	2.5m/m	143	20S	3.5m/m		792	20S	4.0m/m	1,990						
	2.8m/m	172	40S	4.0m/m		862		5.0m/m	2,690			20S			
3/4" 27.2mm	2.0m/m	151		5.0m/m		1,185		6.0m/m	3,205						
	2.1m/m	158	10S	5.2m/m		1,270	40S	7.1m/m	4,518			40S			
	2.5m/m	182	20S	3" 89.1mm		2.0m/m	523	10S	8" 216.3mm			3.0m/m	1,970		
2.9m/m	218	40S	2.5m/m			638						3.5m/m	2,410		
1" 34mm	2.0m/m	195				3.0m/m	748						4.0m/m	2,645	10S
	2.5m/m	236			3.5m/m	930				5.0m/m	3,545				
	2.8m/m	274	10S		4.0m/m	1,014	20S			6.0m/m	4,235				
	3.0m/m	274	20S		5.0m/m	1,395				6.5m/m	4,609	20S			
	3.5m/m	332			5.5m/m	1,470	40S			8.2m/m	7,722	40S			
	3.4m/m	332	40S		3 1/2" 101.6mm	2.0m/m	600			10S	10" 267mm	3.0m/m	2,645		
	4.0m/m	361				2.5m/m	732						3.5m/m	3,240	
1 1/4" 42.7mm	2.0m/m	248				3.0m/m	858						4.0m/m	3,560	10S
	2.5m/m	300		3.5m/m		1,068		5.0m/m	4,605						
	2.8m/m	350	10S	4.0m/m		1,165	20S	6.0m/m	5,505						
	3.0m/m	350	20S	5.0m/m		1,550		6.5m/m	5,987			20S			
	3.5m/m	427		5.7m/m		1,840	40S	9.3m/m	10,850			40S			
	3.6m/m	448	40S	6.0m/m		1,840		3.0m/m	3,155						
	4.0m/m	465		4" 114.3mm		2.0m/m	676	10S	12" 318.5mm			3.5m/m	3,870		
1 1/2" 48.6mm	2.0m/m	281				2.5m/m	826						4.0m/m	4,250	5S
	2.5m/m	341			3.0m/m	969				4.5m/m	4,950	10S			
	2.8m/m	398	10S		3.5m/m	1,206				5.0m/m	5,500				
	3.0m/m	398	20S		4.0m/m	1,316	20S			6.0m/m	6,580				
	3.5m/m	491			5.0m/m	1,750				6.5m/m	7,128	20S			
	3.7m/m	536	40S		6.0m/m	2,080	40S			10.3m/m	14,373	40S			
	4.0m/m	536													

備註：美規 ASTM 312 之外徑、厚度與上表所列不盡相同，估價時請另行來電洽詢。

## 壓著不銹鋼管

### JIS G3448 輕量型不銹鋼配管

吋吋稱呼	外徑 mm	厚度 mm	每米單價
13	15.88	0.8	116
20	22.22	1.0	189
25	28.58	1.0	246
30	34.00	1.2	343
40	42.70	1.2	434

吋吋稱呼	外徑 mm	厚度 mm	每米單價
50	48.60	1.2	497
60	60.50	1.5	762
75	76.30	1.5	965
80	89.10	2.0	1,428
100	114.30	2.0	1,839